



NEW PRODUCT AT REDNECK. SAME GREAT SERVICE.

SLIDER360

ANCHOR ANYTHING ANYWHERE

The revolutionary Slider360 is the most versatile cargo control system available for utility trailers and flatbed goosenecks! The unique design allows the D-Ring or winch to be placed anywhere along the length of the trailer.

SAVE TIME AND MONEY WITH:

- Stake pocket, angle-iron mountable, tube-top mountable available in both D-Ring & Winch configurations
- Highly flexible anchor point system
- Interchangeable between multiple trailers
- Fits Horizontal and Vertical Angle Iron Frames
- Large contact area prevents twisting of straps and dampens vibrations
- No need for bolt holes or welding - adjustable to load dimensions



PART #	REF #	DESCRIPTION	PICTURE NO.
SLDR-ANGL-W	404502	ANGLE IRON MOUNTABLE WINCH FOR 2" STRAP, 10K	1
SLDR-ANGL-D	404501	ANGLE IRON MOUNTABLE D-RING, 10K	2
SLDR-STAK-W	404506	STAKE POCKET WINCH FOR 2" STRAP, 10K	3
SLDR-STAK-D	404505	STAKE POCKET D-RING, 10K	4
SLDR-TUB-W	404504	TUBE-TOP MOUNTABLE WINCH FOR 2" STRAP, 10K	5
SLDR-TUB-D	404503	TUBE-TOP MOUNTABLE D-RING, 10K	6

VISIT US AT REDNECK-TRAILER.COM

CALL US AT 1-877-9REDNECK

SLIDER 360

ANCHOR ANYTHING ANYWHERE



Angle Iron w/ Swivel Winch

Part # SLDR-ANGL-W Ref # 404502

Maximum Frame Thickness: 1"

Minimum Frame Thickness: -0"

Breaking Strength: 10,000 LBS

Working Load Limit: 5,000 LBS

Standard Pack Size: 8



Stake w/ Swivel Winch

Part # SLDR-STAK-W Ref # 404506

Fits most stake pockets for most trailer manufacturers.

Locking Pin

Standard Pack Size: 8



Tube-Top w/ Swivel Winch

Part # SLDR-TUB-W Ref # 404504

Maximum Frame Thickness: 3 1/8"

Minimum Frame Thickness: 1 3/4"

Breaking Strength: 10,000 LBS

Working Load Limit: 5,000 LBS

Standard Pack Size: 8



Angle Iron w/ Swivel D-Ring

Part # SLDR-ANGL-D Ref # 404501

Maximum Frame Thickness: 1"

Minimum Frame Thickness: -0"

Breaking Strength: 10,000 LBS

Working Load Limit: 5,000 LBS

Standard Pack Size: 8



Stake w/ Swivel D-Ring

Part # SLDR-STAK-D Ref # 404505

Fits most stake pockets for most trailer manufacturers.

Locking Pin

Standard Pack Size: 8



Tube-Top w/ Swivel D-Ring

Part # SLDR-TUB-D Ref # 404503

Maximum Frame Thickness: 3 1/8"

Minimum Frame Thickness: 1 3/4"

Breaking Strength: 10,000 LBS

Working Load Limit: 5,000 LBS

Standard Pack Size: 8

The revolutionary Slider360 gives you the freedom to create a new anchor point each time you secure a load. That means the D-Ring or winch is exactly where you want it every time.

The Slider360 creates custom anchor points for: Utility Trailers, Gooseneck Trailers, Work Truck Flatbeds, Pickup Truck Racks, Scaffolding, etc.

VISIT US AT REDNECK-TRAILER.COM

CALL US AT 1-877-9REDNECK